# Consumer Confidence Report Certification Form (To be submitted with a copy of the CCR)

Water System Name:		Furnace Creek							
Water System Number: 1410505			1410505						
The water system named above hereby certifies that its Consumer Confidence Report was distributed on 6/25/2013 (date) to customers (and appropriate notices of availability have been given). Further, the system certifies that the information contained in the report is correct and consistent with the compliance monitoring data previously submitted to the California Department of Public Health.									
Certified by:		: Name:		Thomas Buck		•			
		Signatu	ıre:	ga Bu					
		Title:		Utility Supervisor					
		Phone ?	Number:	(760) 786-3264	D	Pate: 4-15-2013			
	that ap	oply and fill-i	n where ap	ppropriate:	•	plete this page by checking all			
Ш	CCR was distributed by mail or other direct delivery methods (attach description of other direct								
		ry methods us	•	1		4 0 11 C FL 4 1			
CCR was distributed using electronic delivery methods described in the Guidance for l									
		•		- '	er systems utilizin	g electronic delivery methods			
		complete the s				Those offerts included the			
				ed to reach non-our	paying consumers	. Those efforts included the			
	10110	wing methods		following LIPI : waxa	.,				
	Posting the CCR at the following URL: www								
	Mailing the CCR to postal patrons within the service area (attach zip codes used)								
	Advertising the availability of the CCR in news media (attach copy of press release)								
		Publication of the CCR in a local newspaper of general circulation (attach a copy of the							
	published notice, including name of newspaper and date published)  Posted the CCR in public places (attach a list of locations)								
			•	• '	•	serving several persons such			
	Delivery of multiple copies of CCR to single-billed addresses serving several persons, sur as apartments, businesses, and schools								
			community	ty organizations (attach a list of organizations)					
		Publication	of the CCI	R in the electronic cit	y newsletter or ele	ectronic community newsletter			
<del></del>			ttach a cop	by of the article or notice)					
		nnouncem	ncement of CCR availability via social media outlets (attach list of social						
		media outlet	s utilized)						
		Other (attacl	a list of c	other methods used)					
	For sy	For systems serving at least 100,000 persons: Posted CCR on a publicly-accessible internet site at							
_	the following URL: www								
	For privately-owned utilities: Delivered the CCR to the California Public Utilities Commission								

## **Consumer Confidence Report Electronic Delivery Certification**

er systems utilizing electronic distribution methods for CCR delivery must complete this page by king all items that apply and fill-in where appropriate.											
Water system mailed a notification that the CCR is available and provides a direct URL to the on a publicly available website where it can be viewed (attach a copy of the mailed notification). URL: www.											
Water system emailed a notification that the CCR is available and provides a direct URL of CCR on a publicly available site on the Internet where it can be viewed (attach a copy of emailed CCR notification). URL: www											
Water system emailed the CCR as an electronic file email attachment.  Water system emailed the CCR text and tables inserted or embedded into the body of an email, n as an attachment (attach a copy of the emailed CCR).											
Requires prior CDPH review and approval. Water system utilized other electronic delivery meth that meets the direct delivery requirement.											
ide a brief description of the water system's electronic delivery procedures and include how the r system ensures delivery to customers unable to receive electronic delivery.											
 · · · · · · · · · · · · · · · · · · ·											

This form is provided as a convenience and may be used to meet the certification requirement of section 64483(c), California Code of Regulations.

### Death Valley National Park Maintenance Division Water System Operations Death Valley, Ca 92328 June of 2013

Consumer Confidence Report Furnace Creek Water System

#### Dear Water System Customer:

Safe and reliable drinking water supplies are one of the most important resources we have available to us. Here at the National Park Service Death Valley Water System Operations we're committed to providing safe drinking water supplies to our customers that meets or exceeds the standards of quality. In an effort to keep our customers thoroughly informed about the quality of our water supplies, we provide this annual report. The following water quality information can be used for future reference in addressing any questions that you may have regarding your drinking water.

The Furnace Creek Community water supply is collected from three wells located one mile east of the two million gallon tank on the alluvial fan. The system capacity is approximately one million gallons per day. Source water is 86 degrees. Tap water will often exceed 100 degrees because of the intense heat penetration through the ground to the pipes during hot weather.

The water is considered moderately mineralized consisting of sodium, calcium and magnesium, salts and bicarbonate, sulfates, fluoride, arsenic and chloride. The water is considered high silica water in which amorphous silica and magnesium silicate deposits could create serious problems by fouling surfaces of water handling equipment. This type of silica scale is very tenacious and difficult to remove.

Specific water quality data relating to system water supplies can be found in Table 1 of this report. All water naturally contains a variety of dissolved mineral and organic substances and the California Department of Health Serves has adopted drinking water standards that establish limits that may affect health or aesthetic qualities of water.

The California Department of Heath Services (DHS) sets the drinking water standards and has determined that fluoride is a health concern at certain exposure levels. Fluoride occurs naturally in combination with other elements such as, sodium fluoride (NaF) or sodium silicofluoride (Na<sup>2</sup>SiF). All fluoride compounds dissociate to yield fluoride ion when the compounds come in contact with water. Studies dating back to the early 20<sup>th</sup> century have confirmed that drinking water containing fluoride ion concentrations greater than 2.0 mg/L have caused dental flourosis. Dental flourosis is when the enamel of human teeth becomes mottled or discolored. The degree of

discoloration increases with the increase of fluoride in the water. The DHS has set the drinking water standard for fluoride at 2.0 parts per million (2 ppm) to protect against the risk of adverse health effects. Drinking water that meets this standard is associated with little or none of this risk and should be considered safe. Arsenic levels have been reduced to a Maximum Contaminate Level (MCL) of 10 parts per billion (10 ug/l) and it is our goal to exceed these levels.

In cooperation with the Department of Health Services, Division of Drinking Water, the National Park Service in Death Valley has a Reverse Osmosis Water Treatment Plant for the Furnace Creek water system to address the Fluoride and Arsenic regulations. Reverse Osmosis reduces the dissolved solids in the water by a filtration process that uses pressure to force the water through a membrane, retaining the solute (high total dissolved solids) on one side and allowing the pure solution to pass to the other side. By applying a pressure in excess of the Osmotic pressure a clean pure product can be achieved. All tests to date have proved our R.O. Plant exceeds requirements set by the California State Department of Health.

Samples of water are collected twice monthly for bacterial testing by the Inyo County Health Department. All water supplied to the public is disinfected with chlorine. This insures all harmful bacteria are removed. Water is tested daily for chlorine residuals to continuously monitor and control chlorine performance and to also alert personnel if problems occur.

We would like to encourage managers, landlords, employers, schools, etc to distribute this water quality report to individuals who may be non-billed water users to assure the broadest distribution of this information possible. The National Park Service will provide additional copies at no charge. Again, we would like to restate our commitment towards providing safe drinking water to all our customers. If you have any questions please contact us at the Cow Creek Maintenance offices during regular business hours: Monday through Friday 7:00 am to 3:30 p.m. at (760) 786-3264.

#### Table 1

#### Terms and abbreviations used below:

- Public Health Goal (PHG): The level of a contaminant in drinking water below which there is no
  known or expected risk to health. PHGs are set by the California Environmental Protection Agency
- Maximum Contaminant Level Goal (MCLG): The level of a contaminant in drinking water below
  which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental
  Protection Agency.
- Maximum Contaminant Level (MCL): The highest level of a contaminant that is allowed in drinking
  water. Primary MCLs are set as close to the PHGs (MCLGs) as is economically and technologically.
  Secondary MCLs are set to protect odor, taste, and appearance of drinking water.
- Regulatory Action Level (AL): The concentration of a contaminant which, when exceeded, triggers treatment or other requirements that a water system must follow.
- NA: not applicable ND: not detectable PPB: parts per billion PPM: parts per million
- mg/L: milligrams per liter pCi/I: picocuries per liter ug/L: micrograms per liter

Thomas Buck Water Treatment Supervisor

#### Death Valley National Park / Furnace Creek Water System

#### Inorganic Chemicals /

Inorganic Chemicals / Metals		MCL	RAW	FINAL		
Metais		IVICE	MAY	FINAL		·
Atuminum	ppm	0.002	ND	ND	Erosion of natural deposits; Discharge from	m refineries and factories; Runoff from landfills; Runoff from cropland
Antimony	ppm	0.006	ND	ND	Discharge from petroleum refineries; fire r	•
Arsenic	ppm	0.01	27	0.006	Erosion of natural deposits; Runoff from o	rchards; Runoff from glass and electronics production wastes
Barium	ррга	2	ND	ND	Discharge of drilling wastes; Discharge fro	om metal refineries; Erosion of natural deposits
Beryllium	ppm	0.004	ND	ND	Discharge from metal refineries and coal-t	burning factories; Discharge from electrical, aerospace, and defense industries
Cadmium	ppm	0.005	ND	ND		natural deposits; Discharge from metal refineries; Runoff from waste batteries and paints
Chromium	ppm	0.1	ND	ND	Discharge from steel and pulp mills; Erosk	
Copper	ppm	1.3	ND	ND		; Erosion of natural deposits; Leaching from wood preservatives
Cyanide	ppm	0.15	ND	ND	Discharge from steel/metal factories; Disc	
Fluoride	ppm	2	3.6	0.98	-	e which promotes strong teeth; Discharge from fertilizer and aluminum factories
Lead	ppm	0.015	ND	ND	Corrosion of household plumbing systems;	
Mercury	ppm	0,002	ND	ND	· · · · · · · · · · · · · · · · · · ·	m refineries and factories; Runoff from landfills; Runoff from cropland
Nickel	ppm	0.001	ND	ND	·	m refineries and factories; Runoff from landfills; Runoff from cropland
Selenium	ppm	0.05	ND	ND		eries; Erosion of natural deposits; Discharge from mines
Silver	ppm	0.001	ND	ND		m refineries and factories; Runoff from landfills; Runoff from cropland
Thallium	ppm	0.002	ND	ND	•	large from electronics, glass, and drug factories
Vanadium	ppm	0.003	ND	ND		m refineries and factories; Runoff from landfills; Runoff from cropland
Valladidili	ppm	0.003	ND	NO	Eloson of ratural deposits, Discratige from	iii letarenes and sactories, Adio)) from enotals, Adio)) from cropana
Nitrate / Nitrite						
Nitrate	ppm	10	ND	ND	Runoff from fertilizer use; Leaching from s	eptic tanks, sewage; Erosion of natural deposits
Nitrite	ppm	1	ND	ND		eptic tanks, sewage; Erosion of natural deposits
Radiological						
Gross Alpha emitters	pCVL	15	9	9	Erosion of natural deposits	
Radium	ppb	5	0	0	Erosion of natural deposits	
Regulated SOC's						
					,	•
All tested SOC's results were non	detectible					
Regulated VOC's						
All tested VOC's results were non	dataatibla					
All lested VOCs results were north	detectible					
Secondary / GP						•
Bicarbonate Alkalinity	ppm	NR	370	122		
Calcium	ppm	NR	45	15		
Choride	ppm	500	32	11		
Hardness (Total) as CACO3	ppm	NR	170	56		
Magnesium	ppb	50	20	7		
pH	ppm	6.5-8.5	7.6	7.6		
Sodium	ppm	500	150	50		
Sulfate	ppm	500	160	53		
Total Disolved Solids		1000		190		
Total Disolved Solids	ppm	1000	600	190		
Microbiological Contaminants						
Contaminants						•
Total Coliform	P/A	Р	Р	Α	Naturally present in the environment	
Total Coliform Monthly % Pos	%	5%	0%	0%	Naturally present in the environment	
Fecal Coliform	P/A	Р	A	A	Human and animal fecal waste	
E. Cali	P/A	P	A	Ä	Human and animal fecal waste	
Disinfectants and	·					
Disinfection						
Byproducts						
Object					102 122	•
Chlorine	ppm	4	0	0.9	Water additive used to control microbes	
Haloacetic Acid (HAA5)	ppb	50	NT	ND	Disinfectant By-Product	
Total Trihalomethanes(TTHM's)	ppb	80	NT	ND	Disinfectant By-Product	
Turbidity	NTU	1	0.35	0.1	Soil runoff	

MCL Maximum Contaminant Level RAW Source of Water

Final Finished Water that is available for the consumer

ND No Detection
NR No Regulation
NT Not Tested

NTU Nephelometric Turbidity Units / Clarity of the water

P/A Presence / Absence

pCi/L Picocuries per Liter / standard measure for the intensity of radioactivity / one trillionith of one curie

ppm Parts per million / miligrams per liter / mg/L ppb Parts per billion / micrograms per liter / ug/L